

Union Thresherman, Incorporated

P.O. Box 71 Manawa, WI 54949

Website: www.symcoutc.com

Farm Rules

CLASSES - Any year - 6500, 7500, 8500, 9500, 10500, 12500, and 14500

Farm Pulling Rules

- 1. Any year farm tractor allowed
- 2. Anyone caught tampering with another tractor will be disqualified
- 3. Tractors must be operated in a safe manner at all times
- 4. No crawlers, tire chains or duals
- 5. Hitch point can not be higher than 20" or closer than 18" from center of rear axle. All 3 point hitches must be locked from moving! ABSOLUTELY NO FLOATING DRAWBARS!!!
- 6. Any tractor violating track boundaries must take distance at that point
- 7. Tractors must stop upon red flag or will be disqualified. If track stops pull for any reason puller must take that distance
- 8. Any drivers between 14 & 18 years old must have parental signature and tractor safety class certificate with them NO EXCEPTIONS!
- 9. Anything that falls off the tractor before the pin is pulled will disqualify the tractor and pull. TRACK JUDGES RULING IS FINAL ON ALL AREAS OF DISPUTE NOT COVERED IN THESE RULES

Stock Farm Class - 6 MPH

- 1. Must be a "farm" tractor. Original frame, for example, rear end, transmission, pto etc. installed and in working order
- 2. Stock injection pump and, if so equipped, tractor must be equipped with an OEM turbo
- 3. No water injection
- 4. Stock engine RPM's only
- 5. 20.8 max tire width, no cut or sharpened tires! (TRUE road worn is OK)
- 6. No FWD or front assists unless tractor is unhooked and turned off
- **7.** TA's or "shift on the go" is ok
- 8. No alcohol, must run on gasoline, LP or diesel. Must run on the fuel it was originally designed for

Improved Farm Class – 18 MPH

- 1. Turbo is limited to single turbo no larger than 2.8" inlet size. No 3" chargers or Bigfoot exhaust housing
- 2. 3000 RPM's max! Anyone caught over will be disqualified
- 3. 20.8" Max tire width, any cut is ok
- 4. ALL TRACTORS MUST HAVE SAFETY EQUIPMENT Wheelie bars, air shutoff, fire extinguisher, cross bolts in exhaust is strongly recommended, 2 3/8" bolts, 90 degree x 1" apart and no more than 10" from turbo outlet
- 5. No alcohol. Must run fuel tractor was originally designed for
- 6. No component tractors. Must run an agricultural real end
- 7. No rain caps of curved exhaust pipes....vertical discharge only
- 8. All tractors will be tached and must remain in the staging area prior to bring hooked!

CLASSES ARE SUBJECT TO CHANGE THE DAY OF THE PULL